## (19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 1 September 2005 (01.09.2005)

## (10) International Publication Number WO 2005/081286 A1

(51) International Patent Classification7:

H01L 21/00

(21) International Application Number:

PCT/EP2005/050611

(22) International Filing Date: 11 February 2005 (11.02.2005)

(25) Filing Language:

(26) Publication Language:

English

(30) Priority Data: 04003270.8

13 February 2004 (13.02.2004)

- (71) Applicant (for all designated States except US): SHELL SOLAR GMBH [DE/DE]; Otto Hahn Ring 6, D-81739 München (DE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): MÜNZER, Adolf [DE/DE]; Stadionstr. 152, D-85717 Unterschleissheim
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR APPLYING A LIQUID DOPANT SOLUTION ON A WAFER



(57) Abstract: Device (1) for applying a liquid dopant solution on a wafer (3), comprising a dopant distribution device (5), a rotatable horizontally translatable dopant-transfer roll (7) between a first roll position (15) and a second roll position, and a work table (9) for holding the wafer (3), wherein the distribution device (5) comprises a dopant-transfer block (20) and a fluid container (24) having an open side enclosed by an edge (26), which open side is directed to the dopant-transfer block (20), wherein the block holder (21) is horizontally translatable between a first block position in which the dopant-transfer block is under the open side of the fluid container and a second block position (31) in which the dopant-transfer block (20) has contacted the rotatable dopant-transfer roll (7) in its first roll position (15), wherein during normal operation in the second roll position the rotatable dopant-transfer roll (7) has contacted the wafer (3) to provide dopant solution onto the surface of the wafer (3).